

CLAIMS

We claim:

- 1 1. A seat assembly for a motor vehicle having a tub disposed at least partially in a
2 floor of the vehicle, the seat assembly comprising:
3 a seat cushion translatable on at least one track to a position generally above the
4 tub, the seat cushion being stowable in the tub.

- 1 2. The seat assembly of claim 1 wherein the at least one track is disposed generally
2 laterally in the vehicle.

- 1 3. The seat assembly of claim 1 wherein the seat cushion has an underside, and the
2 underside presents a load floor when the seat cushion is stowed in the tub.

- 1 4. The seat assembly of claim 3 wherein the load floor is generally even with the
2 floor of the vehicle.

- 1 5. The seat assembly of claim 1 wherein the seat cushion is rotatable about an axis
2 generally perpendicular to the at least one track.

- 1 6. The seat assembly of claim 1 further comprising at least one leg extending
2 between the seat cushion and the at least one track.

1 7. The seat assembly of claim 6 wherein the at least one leg is pivotably connected
2 to the seat cushion.

1 8. The seat assembly of claim 6 wherein the at least one leg is releasably connected
2 to the at least one track.

1 9. The seat assembly of claim 6 further comprising at least one second leg connected
2 to the seat cushion, the at least one second leg being disposed inboard in the vehicle from the at
3 least one leg.

1 10. A seat assembly for a motor vehicle having a floor, the seat assembly comprising:
2 at least one track disposed generally laterally in the vehicle;
3 a tub disposed at least partially in the floor; and
4 a seat cushion translatable on the at least one track to a position generally above
5 the tub, the seat cushion being stowable in the tub.

1 11. The seat assembly of claim 10 wherein the seat cushion has an underside, and the
2 underside presents a load floor when the seat cushion is stowed in the tub.

1 12. The seat assembly of claim 11 wherein the load floor is generally even with the
2 floor of the vehicle.

1 13. The seat assembly of claim 10 wherein the seat cushion is rotatable about an axis
2 generally perpendicular to the at least one track.

1 14. The seat assembly of claim 10 further comprising at least one leg extending
2 between the seat cushion and the at least one track.

1 15. The seat assembly of claim 14 wherein the at least one leg is pivotably connected
2 to the seat cushion.

1 16. The seat assembly of claim 15 wherein the at least one leg is releasably connected
2 to the at least one track.

1 17. The seat assembly of claim 14 further comprising at least one second leg
2 connected to the seat cushion, the at least one second leg being disposed inboard in the vehicle
3 from the at least one leg.